

# Depth to Time Report

Company: Chevron  
Well: KC 151 #3

Job Ref. No.  
1232600

## Client and Well Information

Company: Chevron  
Well: KC 151 #3  
Field: Keathley Canyon 151  
County: Offshore **Levels using shuttle #1 (top) of each 4-shot grouping**  
State: Louisiana  
API Number: 60-808-40009  
Logging Date: 17-May-2005

## Survey Information

SRD: 0.0 m      KB elevation: 13.1 m      GL elevation: -1321.9 m  
Source Type: Airgun  
Source Depth below KB: 16.1 m  
Source Distance from Wellhead: 21.3 m  
Source Azimuth from North: 340.0 deg  
Velocity of Medium (Source to Sensor): 1524 m/s  
Velocity of Medium (Source to SRD): 1524 m/s

VERTICAL DEPTH FROM SRD m	TWO WAY TIME AT +00 m ms	TWO WAY TIME AT +05 m ms	TWO WAY TIME AT +10 m ms	TWO WAY TIME AT +15 m ms	TWO WAY TIME AT +20 m ms	TWO WAY TIME AT +25 m ms	TWO WAY TIME AT +30 m ms	TWO WAY TIME AT +35 m ms	TWO WAY TIME AT +40 m ms	TWO WAY TIME AT +45 m ms
0	0.0	6.4	13.1	19.7	26.4	33.0	39.5	46.1	52.8	59.4
50	66.1	72.5	79.2	85.8	92.5	99.1	105.6	112.2	118.9	125.5
100	132.2	138.8	145.3	151.9	158.6	165.2	171.9	178.3	185.0	191.6
150	198.3	204.9	211.4	218.0	224.7	231.3	238.0	244.6	251.1	257.7
200	264.4	271.0	277.7	284.1	290.8	297.4	304.1	310.7	317.2	323.8
250	330.4	337.1	343.7	350.4	356.8	363.5	370.1	376.8	383.4	389.9
300	396.5	403.2	409.8	416.5	422.9	429.6	436.2	442.9	449.5	456.0
350	462.6	469.3	475.9	482.6	489.2	495.7	502.3	509.0	515.6	522.3
400	528.7	535.4	542.0	548.7	555.3	561.8	568.4	575.1	581.7	588.4
450	595.0	601.5	608.1	614.8	621.4	628.1	634.5	641.2	647.8	654.4
500	661.1	667.5	674.2	680.8	687.5	694.1	700.8	707.2	713.9	720.5
550	727.2	733.8	740.3	746.9	753.6	760.2	766.9	773.3	780.0	786.6
600	793.3	799.9	806.4	813.0	819.7	826.3	833.0	839.6	846.1	852.7
650	859.4	866.0	872.7	879.1	885.8	892.4	899.1	905.7	912.2	918.8
700	925.5	932.1	938.8	945.4	951.9	958.5	965.2	971.8	978.5	984.9
750	991.5	998.2	1004.8	1011.5	1017.9	1024.6	1031.2	1037.9	1044.5	1051.2

# Depth to Time Report

Company: Chevron  
Well: KC 151 #3

Job Ref. No.  
1232600

VERTICAL DEPTH FROM SRD m	TWO WAY TIME AT + 00 m ms	TWO WAY TIME AT + 05 m ms	TWO WAY TIME AT + 10 m ms	TWO WAY TIME AT + 15 m ms	TWO WAY TIME AT + 20 m ms	TWO WAY TIME AT + 25 m ms	TWO WAY TIME AT + 30 m ms	TWO WAY TIME AT + 35 m ms	TWO WAY TIME AT + 40 m ms	TWO WAY TIME AT + 45 m ms
800	1057.6	1064.3	1070.9	1077.6	1084.2	1090.7	1097.3	1104.0	1110.6	1117.3
850	1123.7	1130.4	1137.0	1143.7	1150.3	1156.8	1163.4	1170.1	1176.7	1183.4
900	1190.0	1196.5	1203.1	1209.8	1216.4	1223.1	1229.5	1236.2	1242.8	1249.5
950	1256.1	1262.6	1269.2	1275.9	1282.5	1289.2	1295.8	1302.3	1308.9	1315.5
1000	1322.2	1328.8	1335.3	1341.9	1348.6	1355.2	1361.9	1368.3	1375.0	1381.6
1050	1388.3	1394.9	1401.6	1408.0	1414.7	1421.3	1428.0	1434.6	1441.1	1447.7
1100	1454.4	1461.0	1467.7	1474.1	1480.8	1487.4	1494.1	1500.7	1507.4	1513.8
1150	1520.5	1527.1	1533.8	1540.4	1546.9	1553.5	1560.2	1566.8	1573.5	1579.9
1200	1586.6	1593.2	1599.9	1606.5	1613.0	1619.6	1626.3	1632.9	1639.5	1646.2
1250	1652.6	1659.3	1665.9	1672.6	1679.2	1685.7	1692.3	1699.0	1705.6	1712.3
1300	1718.7	1725.4	1732.0	1738.7	1745.3	1752.0	1758.4	1765.1	1771.7	1778.4
1350	1785.0	1791.5	1798.1	1804.8	1811.4	1818.1	1824.5	1831.2	1837.8	1844.5
1400	1851.1	1857.8	1864.2	1870.9	1877.5	1884.2	1890.8	1897.3	1903.9	1910.6
1450	1916.8	1923.0	1929.2	1935.3	1941.7	1948.0	1953.9	1960.0	1966.4	1972.6
1500	1978.8	1984.8	1990.8	1996.7	2002.3	2008.0	2013.7	2019.5	2025.0	2030.5
1550	2036.2	2041.8	2047.4	2052.9	2058.5	2064.2	2070.0	2075.7	2081.4	2087.0
1600	2092.8	2098.5	2104.2	2110.0	2115.5	2121.3	2127.0	2132.7	2138.4	2144.0
1650	2149.8	2155.5	2161.0							