





DVDM Calibrated, Filtered Gamma Ray (GRMA_FILT)	
0	150
(GAPI)	
Rate of Penetration, Averaged over Last 5ft (ROP5_RM)	
100	0
(M/HR)	

ARC Blended Phase-Shift Resistivity 16-in. (P16B)	
0	10
(OHMM)	
ARC Blended Phase-Shift Resistivity 40-in. (P40B)	
0	10
(OHMM)	
ARC Amplified Blended Phase-Shift Resistivity 40-in (P40B)	
0	2
(OHMM)	
ARC Blended Attenuation Resistivity 40-in. (A40B)	
0	10
(OHMM)	

ARC Attenuation Conductivity 40-in. at 2 MHz (A40H_COND)	
4000	0
(MM/M)	
Downhole Annulus Pressure (DHAP)	
1000	2000
(PSI)	
Downhole Annulus Temperature (DHAT)	
0	10
(DEGC)	

IDEAL Version: ID10\_2B\_08  
IDF

Company: Lamont-Doherty Borehole Research



Well: IODP Expedition 311 CAS-05D

Field: Cascadia Margin

Rig: JOIDES Resolution

State: Pacific Ocean

EcoScope Resistivity - Blended

Essoops Resistivity - Dronaca  
1:1200 Measured Depth  
Recorded Mode Log