



**DISCLAIMER**

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

**OTHER SERVICES1**

- OS1: HRLA
- OS2: HLDS
- OS3: DSI
- OS4: FMS
- OS5: HNGS

**REMARKS: RUN NUMBER 1**


Site U0070A, client designation USC 070, was cored for exploration using the RCB system.  
 \*\*\*This site is subcontracted to Shell from LDEO, not a standard USIO/IODP site!\*\*\*  
 Tools were not able to reach TD due to hole obstruction; maximum depth was 258.5mbsf.  
 Centralized tools run using modified MCD chasis as inline centralizer, as per tool sketch.  
 Eccentered / Centered tools decoupled using knuckle joints with a through-wired spacer.  
 HLDS Caliper used for applicable hole size corrections on up log; bit sized used for downlog.  
 Tools conveyed to hole on wireline through drill pipe, as is standard for this riser-less operation.  
 Logs recorded from Drill Floor, but played back with zero reference at sea bed for compatibility with core data.  
 Original sea bed, as measured from drill floor, was 603.0m uncorrected measured depth below drill floor.  
 Heave compensation was not required due to exceptionally calm sea state and favorable weather during logging.  
 MSS run with Deep Reading (DR) sensor only.

RUN 1			RUN 2		
SERVICE ORDER #:			SERVICE ORDER #:		
PROGRAM VERSION:			PROGRAM VERSION:		
FLUID LEVEL:			FLUID LEVEL:		
LOGGED INTERVAL	START	STOP	LOGGED INTERVAL	START	STOP

**EQUIPMENT DESCRIPTION**

RUN 1		RUN 2	
SURFACE EQUIPMENT		SURFACE EQUIPMENT	
WITM (EDTS)-A			

RUN 1		RUN 2	
DOWNHOLE EQUIPMENT		DOWNHOLE EQUIPMENT	
LEH-MT	MDSB_EDTC		45.58
AH-369	Mud Tempe		44.19
	CTEM		43.12
	Gamma Ray		42.55
EDTC-B	EFTB DIAG		44.19
EDTH-B 8528	TelStatus		42.20
EDTC-B 8529	EDTCB Ele		



MAXIMUM STRING DIAMETER 4.50 IN  
 MEASUREMENTS RELATIVE TO TOOL ZERO  
 ALL LENGTHS IN METERS

Client: LDEO / Shell  
 Well: USC 70  
 Field: Baffin Bay  
 State:  
 Country: Greenland


Rig Name: JOIDES Resolution  
 Reference Datum: Sea Floor  
 Elevation: -603.0 m

Drawing Date: 9/23/2012  
 API #:

Production String	(in)	(m)	Well Schematic	(m)	(in)	Casing String

Kelly Bushing Elevation  
Derrick Floor Elevation  
  
Mean Sea Level

-603.0  
-603.0  
  
-592.0



0.0  
33.0

5.500

303.6

9.875

Sea Floor  
Pipe Shoe

Total Depth - Driller

**Schlumberger**

## Up Log

MAXIS Field Log

Company: Lamont Doherty Earth Observatory

Well: Expedition 344S, U0080A (USC70)

### Input DLIS Files

DEFAULT	MSS_LDEO_HRLA_DSI_010LUP	FN:11	PRODUCER	20-Sep-2012 19:23	861.8 M	591.6 M
---------	--------------------------	-------	----------	-------------------	---------	---------

### Output DLIS Files


DEFAULT	MSS_LDEO_HRLA_DSI_028PUP	FN:33	PRODUCER	23-Sep-2012 02:33	259.1 M	-11.4 M
CLIENT	MSS_LDEO_HRLA_DSI_028PUC	FN:34	CUSTOMER	23-Sep-2012 02:33	259.1 M	-11.4 M



### OP System Version: 19C0-187



MSS_LDEO-A	19C0-187	HRLT-B	19C0-187
DSST-B	19C0-187	HLDS	19C0-187
LDSC-B	19C0-187	EDTC-B	SKK-5169-EDTCB


PIP SUMMARY



Time Mark Every 60 S











Top of Obstruction

FR MSS

Gamma Ray (GR_EDTC) (GAPI)	0	150	Tension (TENS) (LBF)	0	5000	Axial Acceleration (MSSZACC_LDEO) (M/S2)	0	20
			High-Res Susceptibility (MSSHSUS_LDEO) (PPM)					
			-5000					
			Dual-Coil Susceptibility (MSSLSUS_LDEO) (PPM)					
			-5000					

PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
DO	System and Miscellaneous	
PP	Depth Offset for Playback Playback Processing	-603.0 M RECOMPUTE

Format: MSS\_Logging Vertical Scale: 1:200 Graphics File Created: 23-Sep-2012 02:33

OP System Version: 19C0-187

MSS_LDEO-A	19C0-187	HRLT-B	19C0-187
DSST-B	19C0-187	HLDS	19C0-187
LDSC-B	19C0-187	EDTC-B	SKK-5169-EDTCB

Input DLIS Files

DEFAULT	MSS_LDEO_HRLA_DSI_010LUP	FN:11	PRODUCER	20-Sep-2012 19:23	861.8 M	591.6 M
---------	--------------------------	-------	----------	-------------------	---------	---------

Output DLIS Files

DEFAULT	MSS_LDEO_HRLA_DSI_028PUP	FN:33	PRODUCER	23-Sep-2012 02:33		
CLIENT	MSS_LDEO_HRLA_DSI_028PUC	FN:34	CUSTOMER	23-Sep-2012 02:33		



Down Log

MAXIS Field Log

Company: Lamont Doherty Earth Observatory Well: Expedition 344S, U0080A (USC70)

Input DLIS Files

DEFAULT	Flip_MSS_LDEO_HRLA_026LUP		PRODUCER	23-Sep-2012 02:30	862.6 M	506.7 M
---------	---------------------------	--	----------	-------------------	---------	---------

Output DLIS Files

DEFAULT	MSS_LDEO_HRLA_DSI_029PUP	FN:35	PRODUCER	23-Sep-2012 02:41	259.2 M	-24.2 M
CLIENT	MSS_LDEO_HRLA_DSI_029PUC	FN:36	CUSTOMER	23-Sep-2012 02:41	259.2 M	-24.2 M

OP System Version: 19C0-187

MSS\_LDEO-A 19C0-187  
DSST-B 19C0-187  
LDSC-B 19C0-187


HRLT-B  
HLDS  
EDTC-B


19C0-187  
19C0-187  
SKK-5169-EDTCB


PIP SUMMARY


Time Mark Every 60 S


		<b>Dual-Coil Susceptibility (MSSL SUS_LDEO)</b>	
-5000		(PPM)	0
		<b>High-Res Susceptibility (MSSH SUS_LDEO)</b>	
-5000		(PPM)	0
<b>Gamma Ray (GR_EDTC)</b>	<b>Tension (TENS)</b>	<b>Axial Acceleration (MSSZACC_LDEO)</b>	
(GAPI)	(LBF)	(M/S <sup>2</sup> )	
0 150	0 5000	0 20	














Gamma Ray (GR_EDTC) (GAPI)	Tension (TENS) (LBF)	Axial Acceleration (MSSZACC_LDEO) (M/S2)
0                      150	0                      5000	0                      20
		High-Res Susceptibility (MSSHSUS_LDEO) (PPM)
		-5000                      0
		Dual-Coil Susceptibility (MSSLSUS_LDEO) (PPM)
		-5000                      0

PIP SUMMARY

Time Mark Every 60 S

### Parameters

DLIS Name	Description	Value
DO	System and Miscellaneous	
PP	Depth Offset for Playback Playback Processing	-603.4    M RECOMPUTE

Format: MSS\_Logging    Vertical Scale: 1:200    Graphics File Created: 23-Sep-2012 02:41

### OP System Version: 19C0-187

MSS_LDEO-A	19C0-187	HRLT-B	19C0-187
DSST-B	19C0-187	HLDS	19C0-187
LDSC-B	19C0-187	EDTC-B	SKK-5169-EDTCB

### Input DLIS Files

DEFAULT	Flip_MSS_LDEO_HRLA_026LUP	PRODUCER	23-Sep-2012 02:30	862.6 M	506.7 M
---------	---------------------------	----------	-------------------	---------	---------

### Output DLIS Files

DEFAULT	MSS_LDEO_HRLA_DSI_029PUP	FN:35	PRODUCER	23-Sep-2012 02:41
CLIENT	MSS_LDEO_HRLA_DSI_029PUC	FN:36	CUSTOMER	23-Sep-2012 02:41

## Calibration and Check Summary

Measurement	Nominal	Master	Before	After	Change	Limit	Units
High Resolution Laterolog Array – B Wellsite Calibration – HRLT M01							
Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45							
HRLT M0-M1 Voltage Plus – 0	0	N/A	-320.1	-319.3	0.7999	9.681	UV
HRLT M0-M1 Voltage Plus – 1	0	N/A	-341.6	-338.6	2.980	9.681	UV
HRLT M0-M1 Voltage Plus – 2	0	N/A	-339.5	-337.3	2.248	9.681	UV
HRLT M0-M1 Voltage Plus – 3	0	N/A	-342.4	-340.5	1.922	9.681	UV
HRLT M0-M1 Voltage Plus – 4	0	N/A	-328.1	-327.0	1.090	9.681	UV
HRLT M0-M1 Voltage Plus – 5	0	N/A	-323.6	-322.7	0.8422	9.681	UV
HRLT M0-M1 Voltage Plus – 6	0	N/A	332.2	329.8	-2.436	9.681	UV
HRLT M0-M1 Voltage Plus – 7	0	N/A	-322.7	-322.7	0	9.681	UV
High Resolution Laterolog Array – B Wellsite Calibration – HRLT M12							
Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45							
HRLT M1-M2 Voltage Plus – 0	0	N/A	1758	1755	-2.932	53.42	UV
HRLT M1-M2 Voltage Plus – 1	0	N/A	1876	1860	-16.31	53.42	UV
HRLT M1-M2 Voltage Plus – 2	0	N/A	1860	1848	-11.92	53.42	UV
HRLT M1-M2 Voltage Plus – 3	0	N/A	1876	1866	-9.832	53.42	UV
HRLT M1-M2 Voltage Plus – 4	0	N/A	1799	1794	-5.057	53.42	UV
HRLT M1-M2 Voltage Plus – 5	0	N/A	1776	1772	-3.489	53.42	UV
HRLT M1-M2 Voltage Plus – 6	0	N/A	-1832	-1820	12.60	53.42	UV
HRLT M1-M2 Voltage Plus – 7	0	N/A	1781	1781	0	53.42	UV
High Resolution Laterolog Array – B Wellsite Calibration – HRLT M23							
Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45							
HRLT M2-M3 Voltage Plus – 0	0	N/A	1745	1741	-3.911	53.42	UV
HRLT M2-M3 Voltage Plus – 1	0	N/A	1875	1857	-17.45	53.42	UV
HRLT M2-M3 Voltage Plus – 2	0	N/A	1860	1847	-13.26	53.42	UV
HRLT M2-M3 Voltage Plus – 3	0	N/A	1879	1868	-10.97	53.42	UV
HRLT M2-M3 Voltage Plus – 4	0	N/A	1796	1789	-6.424	53.42	UV
HRLT M2-M3 Voltage Plus – 5	0	N/A	1773	1769	-4.405	53.42	UV
HRLT M2-M3 Voltage Plus – 6	0	N/A	-1819	-1805	13.85	53.42	UV
HRLT M2-M3 Voltage Plus – 7	0	N/A	1781	1781	0	53.42	UV
High Resolution Laterolog Array – B Wellsite Calibration – HRLT V34							
Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45							
HRLT A3-A4 Voltage Plus – 0	0	N/A	68580	68470	-107.9	2100	UV
HRLT A3-A4 Voltage Plus – 1	0	N/A	73460	72830	-631.8	2100	UV
HRLT A3-A4 Voltage Plus – 2	0	N/A	73170	72710	-458.4	2100	UV
HRLT A3-A4 Voltage Plus – 3	0	N/A	74220	73830	-386.3	2100	UV
HRLT A3-A4 Voltage Plus – 4	0	N/A	70890	70690	-197.9	2100	UV
HRLT A3-A4 Voltage Plus – 5	0	N/A	70020	69890	-123.6	2100	UV
HRLT A3-A4 Voltage Plus – 6	0	N/A	-70280	-69810	468.9	2100	UV
HRLT A3-A4 Voltage Plus – 7	0	N/A	70000	70000	0	2100	UV
High Resolution Laterolog Array – B Wellsite Calibration – HRLT V45							
Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45							
HRLT A4-A5 Voltage Plus – 0	0	N/A	68870	68760	-110.4	2100	UV
HRLT A4-A5 Voltage Plus – 1	0	N/A	73860	73240	-616.3	2100	UV
HRLT A4-A5 Voltage Plus – 2	0	N/A	73540	73080	-459.3	2100	UV
HRLT A4-A5 Voltage Plus – 3	0	N/A	74570	74180	-394.7	2100	UV
HRLT A4-A5 Voltage Plus – 4	0	N/A	71190	70990	-199.9	2100	UV
HRLT A4-A5 Voltage Plus – 5	0	N/A	70310	70180	-130.1	2100	UV
HRLT A4-A5 Voltage Plus – 6	0	N/A	-70670	-70200	471.5	2100	UV
HRLT A4-A5 Voltage Plus – 7	0	N/A	70000	70000	0	2100	UV
High Resolution Laterolog Array – B Wellsite Calibration – HRLT V56							
Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45							
HRLT A5-A6 Voltage Plus – 0	0	N/A	68760	68650	-113.5	2100	UV
HRLT A5-A6 Voltage Plus – 1	0	N/A	73580	72960	-610.8	2100	UV
HRLT A5-A6 Voltage Plus – 2	0	N/A	73290	72840	-458.4	2100	UV
HRLT A5-A6 Voltage Plus – 3	0	N/A	74370	74000	-375.0	2100	UV
HRLT A5-A6 Voltage Plus – 4	0	N/A	71050	70850	-198.5	2100	UV
HRLT A5-A6 Voltage Plus – 5	0	N/A	70190	70050	-145.6	2100	UV
HRLT A5-A6 Voltage Plus – 6	0	N/A	-70390	-69900	494.1	2100	UV
HRLT A5-A6 Voltage Plus – 7	0	N/A	70000	70000	0	2100	UV
High Resolution Laterolog Array – B Wellsite Calibration – HRLT VTP							
Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45							
HRLT A5-A6 Voltage Plus – 0	0	N/A	68440	68340	-100.0	2100	UV

HRLT Torpedo-M0 Voltage - 0	0	N/A	-68440	-68340	106.0	2100	UV
HRLT Torpedo-M0 Voltage - 1	0	N/A	-73930	-73290	640.7	2100	UV
HRLT Torpedo-M0 Voltage - 2	0	N/A	-73610	-73150	462.2	2100	UV
HRLT Torpedo-M0 Voltage - 3	0	N/A	-74670	-74280	396.4	2100	UV
HRLT Torpedo-M0 Voltage - 4	0	N/A	-71250	-71050	203.0	2100	UV
HRLT Torpedo-M0 Voltage - 5	0	N/A	-70360	-70210	147.7	2100	UV
HRLT Torpedo-M0 Voltage - 6	0	N/A	70680	70180	-490.6	2100	UV
HRLT Torpedo-M0 Voltage - 7	0	N/A	-70000	-70000	0	2100	UV

High Resolution Laterolog Array - B Wellsite Calibration - HRLT VBD

Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45

HRLT Bridle#9-M0 Voltage - 0	0	N/A	-68430	-68320	110.2	2100	UV
HRLT Bridle#9-M0 Voltage - 1	0	N/A	-73910	-73280	637.2	2100	UV
HRLT Bridle#9-M0 Voltage - 2	0	N/A	-73590	-73130	456.7	2100	UV
HRLT Bridle#9-M0 Voltage - 3	0	N/A	-74650	-74260	384.8	2100	UV
HRLT Bridle#9-M0 Voltage - 4	0	N/A	-71250	-71040	204.3	2100	UV
HRLT Bridle#9-M0 Voltage - 5	0	N/A	-70340	-70210	134.8	2100	UV
HRLT Bridle#9-M0 Voltage - 6	0	N/A	70650	70160	-490.6	2100	UV
HRLT Bridle#9-M0 Voltage - 7	0	N/A	-70000	-70000	0	2100	UV

High Resolution Laterolog Array - B Wellsite Calibration - HRLT ISO

Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45

HRLT Source Current Plus - 0	0	N/A	285.3	284.9	-0.3990	8.520	UA
HRLT Source Current Plus - 1	0	N/A	281.1	281.1	0	8.520	UA
HRLT Source Current Plus - 2	0	N/A	281.1	281.1	0	8.520	UA
HRLT Source Current Plus - 3	0	N/A	281.1	281.1	0	8.520	UA
HRLT Source Current Plus - 4	0	N/A	281.1	281.1	0	8.520	UA
HRLT Source Current Plus - 5	0	N/A	281.1	281.1	0	8.520	UA
HRLT Source Current Plus - 6	0	N/A	281.1	281.1	0	8.520	UA
HRLT Source Current Plus - 7	0	N/A	281.1	281.1	0	8.520	UA

High Resolution Laterolog Array - B Wellsite Calibration - HRLT MV

Before: 20-Sep-2012 18:03 After: 20-Sep-2012 20:45

HRLT Vertical Voltage PI - 0	0	N/A	-322.3	-321.4	0.8523	9.681	UV
HRLT Vertical Voltage PI - 1	0	N/A	-335.6	-332.5	3.175	9.681	UV
HRLT Vertical Voltage PI - 2	0	N/A	-332.8	-330.4	2.353	9.681	UV
HRLT Vertical Voltage PI - 3	0	N/A	-333.9	-331.9	2.034	9.681	UV
HRLT Vertical Voltage PI - 4	0	N/A	-317.3	-316.2	1.169	9.681	UV
HRLT Vertical Voltage PI - 5	0	N/A	-328.1	-327.2	0.9027	9.681	UV
HRLT Vertical Voltage PI - 6	0	N/A	339.4	336.7	-2.633	9.681	UV
HRLT Vertical Voltage PI - 7	0	N/A	-322.7	-322.7	0	9.681	UV

Hostile Litho-Density Sonde Wellsite Calibration - Background Measurement

Master: 3-Aug-2012 12:38 Before: 20-Sep-2012 18:06 After: 20-Sep-2012 21:14

SS Cs Resolution Bkg	9.000	7.952	8.050	8.000	-0.05026	1.800	%
LS Cs Resolution Bkg	9.000	8.109	8.189	8.101	-0.08724	1.800	%
LSW1 Background	100.0	71.68	71.68	71.86	0.1790	3.000	CPS
LSW2 Background	100.0	68.54	66.66	66.34	-0.3285	3.000	CPS
LSW3 Background	200.0	146.7	145.5	147.5	1.967	6.000	CPS
LSW4 Background	250.0	177.8	179.7	178.5	-1.147	7.500	CPS
LSW5 Background	600.0	409.7	409.8	411.6	1.815	18.00	CPS
SSW1 Background	100.0	81.22	80.50	80.07	-0.4239	3.000	CPS
SSW2 Background	200.0	145.7	143.5	142.3	-1.204	6.000	CPS
SSW3 Background	500.0	389.5	388.2	387.2	-0.9963	15.00	CPS
SSW4 Background	270.0	200.9	200.6	199.1	-1.489	8.100	CPS
SSW5 Background	200.0	146.3	146.0	145.3	-0.7189	6.000	CPS

Hostile Litho-Density Sonde Wellsite Calibration - Aluminum Measurement

Master: 3-Aug-2012 13:08

LSW1 Aluminum	600.0	531.2	N/A	N/A	N/A	N/A	CPS
LSW2 Aluminum	900.0	759.6	N/A	N/A	N/A	N/A	CPS
LSW3 Aluminum	1100	924.3	N/A	N/A	N/A	N/A	CPS
LSW4 Aluminum	580.0	467.3	N/A	N/A	N/A	N/A	CPS
LSW5 Aluminum	570.0	427.7	N/A	N/A	N/A	N/A	CPS
SSW1 Aluminum	2800	2539	N/A	N/A	N/A	N/A	CPS
SSW2 Aluminum	8000	6810	N/A	N/A	N/A	N/A	CPS
SSW3 Aluminum	11600	9419	N/A	N/A	N/A	N/A	CPS
SSW4 Aluminum	5000	3830	N/A	N/A	N/A	N/A	CPS
SSW5 Aluminum	660.0	469.0	N/A	N/A	N/A	N/A	CPS

Hostile Litho-Density Sonde Wellsite Calibration - Lithology Measurement

Master: 3-Aug-2012 13:03

LSW1 Iron	400.0	367.3	N/A	N/A	N/A	N/A	CPS
LSW2 Iron	730.0	618.0	N/A	N/A	N/A	N/A	CPS
LSW3 Iron	1000	815.0	N/A	N/A	N/A	N/A	CPS
LSW4 Iron	520.0	424.5	N/A	N/A	N/A	N/A	CPS
LSW5 Iron	470.0	392.6	N/A	N/A	N/A	N/A	CPS
SSW1 Iron	2100	1845	N/A	N/A	N/A	N/A	CPS
SSW2 Iron	6800	5678	N/A	N/A	N/A	N/A	CPS
SSW3 Iron	10800	8586	N/A	N/A	N/A	N/A	CPS
SSW4 Iron	4600	3500	N/A	N/A	N/A	N/A	CPS
SSW5 Iron	580.0	417.1	N/A	N/A	N/A	N/A	CPS

Hostile Litho-Density Sonde Wellsite Calibration – Caliper Calibration

Before: 3-Aug-2012 13:28

HLDS Caliper Small Ring	12.00	N/A	15.62	N/A	N/A	N/A	IN
HLDS Caliper Large Ring	15.19	N/A	19.44	N/A	N/A	N/A	IN

Enhanced DTS Cartridge Wellsite Calibration – EDTC Accelerometer Calibration

Before: 20-Sep-2012 18:08

EDTC Z-Axis Acceleration	9.810	N/A	9.852	N/A	N/A	N/A	M/S2
--------------------------	-------	-----	-------	-----	-----	-----	------

Enhanced DTS Cartridge Wellsite Calibration – Detector Calibration

Before: 20-Sep-2012 18:08 After: 20-Sep-2012 21:12

Gamma Ray (Jig – Bkg)	159.7	N/A	159.7	162.2	2.544	14.52	GAPI
Gamma Ray (Calibrated)	165.0	N/A	165.0	167.6	2.629	15.00	GAPI

High Resolution Laterolog Array – B / Equipment Identification

Primary Equipment:

HRLT Sonde HRLS – B 768

Auxiliary Equipment:

HRLT lower Housing HRLH – B 968  
 HRLT Lower Cartridge HRLC – B 974  
 HRLT upper Housing HRUH – B 978  
 HRLT Upper Cartridge HRUC – B 764

High Resolution Laterolog Array – B Wellsite Calibration

HRLT M01

Idx	Phase	HRLT M0-M1 Voltage Plus UV	Value	Nominal	Maximum	Minimum
0	Before		-320.1	-322.7	-280.7	-379.7
	After		-319.3			
1	Before		-341.6	-322.7	-280.7	-379.7
	After		-338.6			
2	Before		-339.5	-322.7	-280.7	-379.7
	After		-337.3			
3	Before		-342.4	-322.7	-280.7	-379.7
	After		-340.5			
4	Before		-328.1	-322.7	-280.7	-379.7
	After		-327.0			
5	Before		-323.6	-322.7	-280.7	-379.7
	After		-322.7			
6	Before		332.2	322.7	379.7	280.7
	After		329.8			
7	Before		-322.7	-322.7	-280.7	-379.7
	After		-322.7			
		(Minimum) (Nominal) (Maximum)				

Before: 20-Sep-2012 18:03

After: 20-Sep-2012 20:45

High Resolution Laterolog Array – B Wellsite Calibration

HRLT M12

Idx	Phase	HRLT M1-M2 Voltage Plus UV	Value	Nominal	Maximum	Minimum
0	Before		1758	1781	2095	1549
	After		1755			
1	Before		1876	1781	2095	1549
	After		1860			

2	Before		1860	1781	2095	1549
	After		1848			
3	Before		1876	1781	2095	1549
	After		1866			
4	Before		1799	1781	2095	1549
	After		1794			
5	Before		1776	1781	2095	1549
	After		1772			
6	Before		-1832	-1781	-1549	-2095
	After		-1820			
7	Before		1781	1781	2095	1549
	After		1781			
(Minimum)                      (Nominal)                      (Maximum)						

Before: 20-Sep-2012 18:03  
 After: 20-Sep-2012 20:45

High Resolution Laterolog Array – B Wellsite Calibration						
HRLT M23						
Idx	Phase	HRLT M2-M3 Voltage Plus UV	Value	Nominal	Maximum	Minimum
0	Before		1745	1781	2095	1549
	After		1741			
1	Before		1875	1781	2095	1549
	After		1857			
2	Before		1860	1781	2095	1549
	After		1847			
3	Before		1879	1781	2095	1549
	After		1868			
4	Before		1796	1781	2095	1549
	After		1789			
5	Before		1773	1781	2095	1549
	After		1769			
6	Before		-1819	-1781	-1549	-2095
	After		-1805			
7	Before		1781	1781	2095	1549
	After		1781			
(Minimum)                      (Nominal)                      (Maximum)						

Before: 20-Sep-2012 18:03  
 After: 20-Sep-2012 20:45

High Resolution Laterolog Array – B Wellsite Calibration						
HRLT V34						
Idx	Phase	HRLT A3-A4 Voltage Plus UV	Value	Nominal	Maximum	Minimum
0	Before		68580	70000	82360	60900
	After		68470			
1	Before		73460	70000	82360	60900
	After		72830			
2	Before		73170	70000	82360	60900
	After		72710			

Idx	Phase	HRLT A4-A5 Voltage Plus UV	Value	Nominal	Maximum	Minimum
3	Before		74220	70000	82360	60900
	After		73830			
4	Before		70890	70000	82360	60900
	After		70690			
5	Before		70020	70000	82360	60900
	After		69890			
6	Before		-70280	-70000	-60900	-82360
	After		-69810			
7	Before		70000	70000	82360	60900
	After		70000			
(Minimum) (Nominal) (Maximum)						
Before: 20-Sep-2012 18:03						
After: 20-Sep-2012 20:45						

High Resolution Laterolog Array – B Wellsite Calibration						
HRLT V45						
Idx	Phase	HRLT A4-A5 Voltage Plus UV	Value	Nominal	Maximum	Minimum
0	Before		68870	70000	82360	60900
	After		68760			
1	Before		73860	70000	82360	60900
	After		73240			
2	Before		73540	70000	82360	60900
	After		73080			
3	Before		74570	70000	82360	60900
	After		<b>74180</b>			
4	Before		71190	70000	82360	60900
	After		70990			
5	Before		70310	70000	82360	60900
	After		70180			
6	Before		-70670	-70000	-60900	-82360
	After		-70200			
7	Before		70000	70000	82360	60900
	After		70000			
(Minimum) (Nominal) (Maximum)						
Before: 20-Sep-2012 18:03						
After: 20-Sep-2012 20:45						

High Resolution Laterolog Array – B Wellsite Calibration						
HRLT V56						
Idx	Phase	HRLT A5-A6 Voltage Plus UV	Value	Nominal	Maximum	Minimum
0	Before		68760	70000	82360	60900
	After		68650			
1	Before		73580	70000	82360	60900
	After		72960			
2	Before		73290	70000	82360	60900
	After		72840			
3	Before		74370	70000	82360	60900
	After		74000			

4	Before		71050	70000	82360	60900
	After		70850			
5	Before		70190	70000	82360	60900
	After		70050			
6	Before		-70390	-70000	-60900	-82360
	After		-69900			
7	Before		70000	70000	82360	60900
	After		70000			
			(Minimum)	(Nominal)	(Maximum)	
Before: 20-Sep-2012 18:03						
After: 20-Sep-2012 20:45						

High Resolution Laterolog Array – B Wellsite Calibration						
HRLT VTP						
Idx	Phase	HRLT Torpedo-M0 Voltage Plus UV	Value	Nominal	Maximum	Minimum
0	Before		-68440	-70000	-60900	-82360
	After		-68340			
1	Before		-73930	-70000	-60900	-82360
	After		-73290			
2	Before		-73610	-70000	-60900	-82360
	After		-73150			
3	Before		-74670	-70000	-60900	-82360
	After		-74280			
4	Before		-71250	-70000	-60900	-82360
	After		-71050			
5	Before		-70360	-70000	-60900	-82360
	After		-70210			
6	Before		70680	70000	82360	60900
	After		70180			
7	Before		-70000	-70000	-60900	-82360
	After		-70000			
			(Minimum)	(Nominal)	(Maximum)	
Before: 20-Sep-2012 18:03						
After: 20-Sep-2012 20:45						

High Resolution Laterolog Array – B Wellsite Calibration						
HRLT VBD						
Idx	Phase	HRLT Bridle#9-M0 Voltage Plus UV	Value	Nominal	Maximum	Minimum
0	Before		-68430	-70000	-60900	-82360
	After		-68320			
1	Before		-73910	-70000	-60900	-82360
	After		-73280			
2	Before		-73590	-70000	-60900	-82360
	After		-73130			
3	Before		-74650	-70000	-60900	-82360
	After		-74260			
4	Before		-71250	-70000	-60900	-82360
	After		-71040			

5	Before		-70340	-70000	-60900	-82360
	After		-70210			
6	Before		70650	70000	82360	60900
	After		70160			
7	Before		-70000	-70000	-60900	-82360
	After		-70000			
			(Minimum)	(Nominal)	(Maximum)	
Before: 20-Sep-2012 18:03						
After: 20-Sep-2012 20:45						

High Resolution Laterolog Array – B Wellsite Calibration						
HRLT ISO						
Idx	Phase	HRLT Source Current Plus UA	Value	Nominal	Maximum	Minimum
0	Before		285.3	284.0	334.1	247.0
	After		284.9			
1	Before		281.1	281.1	330.7	244.4
	After		281.1			
2	Before		281.1	281.1	330.7	244.4
	After		281.1			
3	Before		281.1	281.1	330.7	244.4
	After		281.1			
4	Before		281.1	281.1	330.7	244.4
	After		281.1			
5	Before		281.1	281.1	330.7	244.4
	After		281.1			
6	Before		281.1	281.1	330.7	244.4
	After		281.1			
7	Before		281.1	281.1	330.7	244.4
	After		281.1			
			(Minimum)	(Nominal)	(Maximum)	
Before: 20-Sep-2012 18:03						
After: 20-Sep-2012 20:45						

High Resolution Laterolog Array – B Wellsite Calibration						
HRLT MV						
Idx	Phase	HRLT Vertical Voltage Plus UV	Value	Nominal	Maximum	Minimum
0	Before		-322.3	-322.7	-280.7	-379.7
	After		-321.4			
1	Before		-335.6	-322.7	-280.7	-379.7
	After		-332.5			
2	Before		-332.8	-322.7	-280.7	-379.7
	After		-330.4			
3	Before		-333.9	-322.7	-280.7	-379.7
	After		-331.9			
4	Before		-317.3	-322.7	-280.7	-379.7
	After		-316.2			
5	Before		-328.1	-322.7	-280.7	-379.7
	After		-327.2			

6	Before		339.4	322.7	379.7	280.7	
	After		336.7				
7	Before		-322.7	-322.7	-280.7	-379.7	
	After		-322.7				
		(Minimum)	(Nominal)	(Maximum)			
Before: 20-Sep-2012 18:03							
After: 20-Sep-2012 20:45							

**Hostile Litho-Density Sonde / Equipment Identification**







**Primary Equipment:**

Hostile Litho Density Sonde	HLDS - D	45
Hostile Litho Density High Voltage	HLDV - D	45
Gamma Source Radioactive	GSR - Z	8113

**Auxiliary Equipment:**

Hostile Litho Density Pad	HLDP - C	45
Hostile Litho Density High Voltage Housi	HEH - H	47

**Hostile Litho-Density Sonde Wellsite Calibration**

Background Measurement								
Phase	SS Cs Resolution Bkg %	Value	Phase	LS Cs Resolution Bkg %	Value	Phase	LSW1 Background CPS	Value
Master		7.952	Master		8.109	Master		71.68
Before		8.050	Before		8.189	Before		71.68
After		8.000	After		8.101	After		71.86
7.000 (Minimum)			7.000 (Minimum)			55.00 (Minimum)		
9.000 (Nominal)			9.000 (Nominal)			100.0 (Nominal)		
11.000 (Maximum)			11.000 (Maximum)			150.0 (Maximum)		
Phase	LSW2 Background CPS	Value	Phase	LSW3 Background CPS	Value	Phase	LSW4 Background CPS	Value
Master		68.54	Master		146.7	Master		177.8
Before		66.66	Before		145.5	Before		179.7
After		66.34	After		147.5	After		178.5
50.00 (Minimum)			110.0 (Minimum)			140.0 (Minimum)		
100.0 (Nominal)			200.0 (Nominal)			250.0 (Nominal)		
140.0 (Maximum)			290.0 (Maximum)			360.0 (Maximum)		
Phase	LSW5 Background CPS	Value	Phase	SSW1 Background CPS	Value	Phase	SSW2 Background CPS	Value
Master		409.7	Master		81.22	Master		145.7
Before		409.8	Before		80.50	Before		143.5
After		411.6	After		80.07	After		142.3
330.0 (Minimum)			55.00 (Minimum)			100.0 (Minimum)		
600.0 (Nominal)			100.0 (Nominal)			200.0 (Nominal)		
830.0 (Maximum)			150.0 (Maximum)			260.0 (Maximum)		
Phase	SSW3 Background CPS	Value	Phase	SSW4 Background CPS	Value	Phase	SSW5 Background CPS	Value
Master		389.5	Master		200.9	Master		146.3
Before		388.2	Before		200.6	Before		146.0
After		387.2	After		199.1	After		145.3
280.0 (Minimum)			150.0 (Minimum)			110.0 (Minimum)		
500.0 (Nominal)			270.0 (Nominal)			200.0 (Nominal)		
700.0 (Maximum)			380.0 (Maximum)			270.0 (Maximum)		
Master: 3-Aug-2012 12:38			Before: 20-Sep-2012 18:06			After: 20-Sep-2012 21:14		

**Litho-Density Spectroscopy Cartridge - B / Equipment Identification**

**Primary Equipment:**

LDSC Cartridge	LDSC - B	521
----------------	----------	-----

**Auxiliary Equipment:**

LDSC Housing	LDSH - A	319
--------------	----------	-----


**Enhanced DTS Cartridge / Equipment Identification**







Primary Equipment:  
 EDTC Gamma Ray Detector  
 Enhanced DTS Cartridge

EDTG - A/B 77693  
 EDTC - B 8529

Auxiliary Equipment:  
 EDTC Housing

EDTH - B 8528

Enhanced DTS Cartridge Wellsite Calibration		
EDTC Accelerometer Calibration		
Phase	EDTC Z-Axis Acceleration M/S2	Value
Before		9.852
	9.610 (Minimum)      9.810 (Nominal)      10.01 (Maximum)	
Before: 20-Sep-2012 18:08		

Enhanced DTS Cartridge Wellsite Calibration										
Detector Calibration										
Phase	Gamma Ray Background GAPI	Value	Phase	Gamma Ray (Jig - Bkg) GAPI	Value	Phase	Gamma Ray (Calibrated) GAPI	Value		
Before		4.007	Before		159.7	Before		165.0		
After		4.426	After		162.2	After		167.6		
	0 (Minimum)      30.00 (Nominal)      120.0 (Maximum)			145.2 (Minimum)      159.7 (Nominal)      174.2 (Maximum)			150.0 (Minimum)      165.0 (Nominal)      180.0 (Maximum)			
Before: 20-Sep-2012 18:08			After: 20-Sep-2012 21:12							

**Company: Lamont Doherty Earth Observatory**  
**Shell**  
**Well: Expedition 344S, U0070A (USC70)**  
**Field: Baffin Bay**  
**Rig: JOIDES Resolution**  
**Country: USA**

**Schlumberger**

LDEO MSS  
 Magnetic Susceptibility